



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT



The kit includes: four Mini series door-entry phones art. 2702W, a transformer art. 1200, an Extra series external unit designed for 2/4 call buttons art. ET5100, 4 single buttons for Extra entrance panel art. ET9211. The kit can be expanded with another door-entry phone for each user. The external unit can be surface-mounted or flush-mounted using the corresponding accessories supplied with the kit.

AWARDS





KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT

PRODUCTS IN THE KIT



ET5100 EXTRA 4+N ENTRANCE PANEL PREPARED FOR 2/4 BUTTONS

Extra series audio entrance panel with stainless steel cover and nameplate backlighting. To be completed with single button art. ET9211 (pack of 4 units) to offer 4 call buttons, or with double-height button art. ET9210 (pack of 2 units) to offer 2 call buttons. The entrance panel can be surface-mounted or flush-mounted using the relevant accessories supplied. Traditional 4 + N wiring system. Dimensions (W x H x D): 95x165x6.5 mm (flush) - 25 mm (surface).

GENERAL DATA	
Type	Monoblock
Flush-mounted	Yes
Wall-mounted	Yes



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT



2702W 2-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL

MINI series door-entry phone for traditional system with electronic call and key button. Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light.
Dimensions: 105x191x28 mm

GENERAL DATA	
Height (mm)	190
Width (mm)	105
Depth (mm)	28
Product color	White
Type of finishing materials	Plastic
Product weight (g)	260
Wall-mounted	Yes
Desk base-mounted	Yes

COMPATIBLE SYSTEMS	
Traditional system	Yes

AUDIO FEATURES	
Microphone	4mm (Ø), Omnidirectional
Loudspeaker	0.50mm, 0.5W

ELECTRICAL CHARACTERISTICS	
Supply voltage	15÷16VDC
Absorption in stand-by (W)	3
Maximum absorption (W)	6

HARDWARE FEATURES	
Type of buttons	Mechanical
Service buttons	Lock-release



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT

HARDWARE FEATURES

Clamps	S 2 3 4 P1 P2
Total buttons (n°)	2

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP30
Operating temperature (°C)	-5 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	III
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

GENERAL FEATURES

Door opener	Yes
Silent mode (Privacy)	Yes
Ringtone volume control	Yes
Electronic bell	Yes



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT



1200 **TRANSFORMER 10VA 0-230V/0-12V**

Transformer with 230V primary winding, 12V AC / 900 mA secondary winding for continuous use. Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES	
Supply voltage	230 VAC
Applicable to DIN rail	Yes
Number of DIN modules (n°)	3
Max. current delivered (A)	0.9
GENERAL DATA	
Height (mm)	95
Width (mm)	53
Depth (mm)	65
Type of finishing materials	Plastic
Operating temperature (°C)	-5 ÷ 40
COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes
Simplified system	Yes
ELECTRICAL SPECIFICATIONS	
Maximum power delivered (W)	15



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT

ACCESSORIES



ET9151 Flush-mounted box for Extra entrance panel

Flush-mounted box for Extra series external unit art. ET5200.
Dimensions 164.5x93.5x25 mm.



ET9161 Wall bracket for Extra entrance panel

Wall housing for Extra series external unit art. 5200. Dimensions
94x164x19 mm.



1229 EXTENSION SOUNDER

Additional bell for call repetition can be controlled directly from
terminals S- and S+ of the brackets and/or from the telephones.
Surfacemounted or on civil series 503 box. Dimensions: 110X75X29
mm.